

Product Specification Sheet

Custom Window Clings

Custom Window Clings grip smooth glass through surface tension rather than permanent adhesive, making them the only window graphic that removes cleanly every time. Each cling prints on 8 mil low-tack static cling material with a mini-dot backing that prevents air bubbles on application. They're the right choice for any temporary window graphic that needs to come down without a trace.

Material

8 mil low-tack window cling with mini-dot adhesive backing.

Thicker than standard 4 mil vinyl, so the cling lies flat without curling at the edges.

Print Method

UV printing (ink cured instantly by ultraviolet light).

Produces a scratch-resistant, waterproof surface that holds up through multiple removal cycles.

Color Output

Full-color CMYK (cyan, magenta, yellow, and black four-color process).

Reproduces bold graphics, photographs, and fine text across the full printed face.

Finishing

Die-cut to custom shape. Kiss-cut on backing sheet (cut through the cling layer only, leaving the backing intact for easy peeling).

Size Range

Custom sizes up to 58.5 in wide.

Orders wider than 58.5 in ship in multiple panels with alignment guides.

Indoor/Outdoor Rating

Outdoor rated for UV-printed color longevity. Inside-mount application gives the best durability. Exterior-face exposure may shorten usable life depending on climate.

Single/Double-Sided

Single-sided only. Printed face displays outward. Mini-dot backing faces the glass.

Adhesive Type

No permanent adhesive. Static cling holds through surface tension and mini-dot contact points. Removes without residue and repositions on any clean, smooth glass surface.