

Product Specification Sheet

Round Arch Trade Show Booth With Podium

The Round Arch Trade Show Booth With Podium runs a 32mm curved aluminum frame with 210 to 230 GSM polyester tension fabric printed by dye sublimation. It's built for indoor trade shows, conventions, and conference halls where a curved arch silhouette needs to rise above neighboring booth displays. The complete package includes the arch backwall, branded podium, carry cases, and all hardware.

Material

32mm curved aluminum tube frame. Tension fabric graphic panels run 210 to 230 GSM polyester. Heavier GSM holds its shape under frame tension without sagging.

Print Method

Dye sublimation transfers ink into the polyester fibers using heat. Colors will not crack, peel, or fade after washing and reuse.

Color Output

CMYK full-color across arch pillars, curved top beam, and podium front panel. No color limits on gradients or photographic images.

Finishing

Zipper pillowcase covers (fabric sleeves that zip around each frame section, hiding all hardware). Stabilizing feet, connecting clips, and carry cases included.

Size Range

Standard 10 ft x 10 ft booth space. Scales to 10 ft x 20 ft double booth. Podium assembles to 37 in wide by 40 in tall by 17.5 in deep.

Indoor/Outdoor Rating

Indoor use only. Suited for trade show halls, convention centers, and conference venues. Not rated for outdoor weather exposure.

Single/Double-Sided

Single-sided standard for booths placed against a wall. Double-sided available for island booths where attendees approach from both sides.

Weight

Tension fabric panels run 210 to 230 GSM. Full booth with frame and cases weighs roughly 40 to 70 lbs depending on configuration.