Product Specification Sheet

10 ft x 10 ft Inline Trade Show Booth With Backdrop, LED Lights and Podium

This booth runs on a 32mm aluminum snap-button frame with 210 to 230 GSM dye-sublimated tension fabric. Built for indoor trade shows, conventions, and conference halls. Here's the thing: every spec below reflects what ships in the box.

Material

210 to 230 GSM polyester tension fabric.

Polyester stretched over the frame keeps the graphic surface smooth and wrinkle-free with no visible hardware showing through.

Print Method

Dye sublimation.

Ink bonds into the polyester fibers under heat, so color sits inside the fabric and won't crack or peel.

Color Output

CMYK full color.

Cyan, magenta, yellow, and black reproduce photographs, gradients, and detailed brand graphics accurately across the full backwall panel.

Finishing

Zipper pillowcase covers.

The fabric graphic zips around the frame so no hardware shows on the face, and it removes in minutes for washing or replacement.

Size

10 ft x 10 ft booth footprint. Backwall panel runs roughly 79 in wide by 90 to 100 in tall.

Fits a standard single-booth space at most trade shows and conventions.

Indoor/Outdoor Rating

Indoor use only. Rated for trade shows, convention halls, and conference centers.

Not rated for outdoor weather exposure.

Sided

Single-sided standard. Double-sided available for island booth layouts where both faces are visible.

Most first-time exhibitors in a 10 ft x 10 ft space do not need double-sided.

Frame Weight Class

32mm aluminum tubes at 1.1mm wall thickness.

Light enough for two people to carry and assemble, with snap-button joints that hold the structure rigid on the show floor.